CONTACT US

540-825-8334 · sales@bandt-us.com · bandt-us.com

SALES DIRECTORS



BRANDON WHEELER Central p. 918-319-7900 e. bwheeler@bandt-us.com



MARK DELANCELLOTTI West p. 540-229-2599

e. mdelance@bandt-us.com



PERRY HYDE Midwest p. 540-229-1882 e. phyde@bandt-us.com



DENNIS QUINN Mid-Atlantic, New England, Canada p. 540-219-4596 e. dquinn@bandt-us.com

Durability meets Versatility





GARY MOUNTJOY Southeast p. 912-341-9482 e. gmountjoy@bandt-us.com



Built on Quality - Focused on Innovation

Maverick Meter Lids



bandt-us.com

AMI / AMR FRIENDLY

Maverick Lids are made with fiberglass reinforced polypropylene that does not degrade the radio signal from your transmitter. The Thru-Hole allows for any type of AMI/AMR transmitter to be mounted through the lid with the simple addition of a Smart Insert. For those transmitters that will be mounted underneath the lid, the solid lid has brackets and screw holes to secure your transmitter.



EXCEPTIONAL STRENGTH

The fiberglass reinforced polypropylene material provides exceptional strength and can withstand a loading of 20,000 lbs. The unique design of the underside ribbing provides the structural support you need.

PART SERIES	DESCRIPTION	DIAMETER	SKIRT DIAMETER	RIM THICKNESS	WEIGHT	
PLDA-S	Solid	12.25	11.25	0.7		
		12.50	11.25, 11.50, 11.75	0.5 or 0.7	3	
		12.75	11.25, 11.50	0.5	5	
		13.00	11.75	0.5		
PLDA-T	One Recessed Hole	12.25	11.25	0.7	3	
		12.50	11.25, 11.50, 11.75	0.5 or 0.7		
		12.75	11.25, 11.50	0.5		
		13.00	11.75	0.5		





LARGE DIAMETER

For a larger diameter of 21.25" a cast iron ring is used with the 12.25" Maverick lid. The cast Iron ring adds stability and strength while the plastic lid allows for clear AMI/AMR signal transmission.



PART SERIES	RING OUTER DIAMETER	FITS METER FRAME	FITS METER LID	LID TYPE
CULFRR2112A	21.25	MR20	PLDA12.25A7	Solid
CULFRRZTIZA				Thru-Hole